Serial No.: 10/518,697

Docket No.: 28951.2186

IN THE CLAIMS:

1. (Currently Amended) A plasma display panel comprising:

a front panel comprising:

a first substrate;

a first electrode on the first substrate;

a dielectric glass layer covering the first electrode; and

a protective film on the dielectric glass layer, the protective film comprising magnesium oxide (MgO) and an additional oxide, said additional oxide comprising an element with an electronegativity of 1.4 or higher and having a negative charge including at least one of germanium oxide (GeO₂), tin oxide (SnO₂), boron oxide (B₂O₃), silicon oxide (SiO₂) and lead oxide (PbO); and

a back panel on a second substrate comprising:

at least a second electrode;

a barrier rib; and

a phosphor layer,

wherein the protective film and the phosphor layer are arranged facing each other, and form a discharge space partitioned with a barrier rib between the front panel and the back panel.

2. (Canceled).

2

Serial No.: 10/518,697

Docket No.: 28951.2186

3. (Canceled).

4. (Currently Amended) A method for producing a plasma display panel including:

forming a first electrode on a first substrate;

forming a dielectric glass layer to cover the first electrode;

forming a protective film to cover the dielectric glass layer, the protective film

comprising magnesium oxide (MgO) and an additional oxide, said additional oxide comprising

an element with an electronegativity of 1.4 or higher and having a negative charge including at

least one of germanium oxide (GeO₂), tin oxide (SnO₂), boron oxide (B₂O₃), silicon oxide (SiO₂)

and lead oxide (PbO), wherein the process of forming the protective film is selected from the

group consisting of sputtering, vacuum evaporation, and ion plating.

5. (Canceled).

6. (Previously Presented) The plasma display panel of claim 1, wherein the second

electrode is positioned orthogonally to the first electrode.

3

Serial No.: 10/518,697 Docket No.: 28951.2186

7. (Previously Presented) The method of claim 4, further comprising forming a second electrode on a second substrate, wherein the first electrode and the second electrode are arranged orthogonally to each other.